

Intensity distribution of waves transmitted through a multiple scattering medium

Th. M. Nieuwenhuizen and M. C. W. van Rossum
Van der Waals-Zeeman Laboratory, Universiteit van Amsterdam
Valckenierstraat 65, 1018 XE Amsterdam, The Netherlands
 (February 1, 2008)

Abstract

The distributions of the angular transmission coefficient and of the total transmission are calculated for multiple scattered waves. The calculation is based on a mapping to the distribution of eigenvalues of the transmission matrix. The distributions depend on the profile of the incoming beam. The distribution function of the angular transmission has a stretched exponential decay. The total-transmission distribution grows log-normally whereas it decays exponentially.

42.25-p,78.20.Dj,72.10.-d,05.40+j

Transport through mesoscopic systems is a wide field of interest and is studied with a variety of waves: sound, microwaves, electrons, and light. The wave character leads to interference between the transmission channels. This causes large fluctuations. Therefore the observables are not always characterized by mean values, but their entire distribution functions are of interest. This is particularly prominent in the distribution of eigenvalues of the transmission matrix. The eigenvalues have a bimodal distribution peaked around 0 and 1 with a mean value $\ell/L \ll 1$, where ℓ denotes the mean free path and L the thickness of the sample [1–3].

Three distinct transmission quantities can be measured. If a laser illuminates a diffuse medium the transmitted signal consists of speckles. These speckles are the first quantity of interest. The intensities of the speckles obey in first approximation the Rayleigh law, which is a negative exponential distribution. In the mesoscopic regime interference modifies this distribution. The leading correction was derived by Shnerb and Kaveh [4]. Genack and Garcia observed a deviation from the Rayleigh law at large intensities [5]. A crossover to stretched exponential behavior was derived by Kogan *et al.* [6].

The second quantity is the total transmission. It is obtained by integrating over the outgoing surface, thus collecting all speckles. When adding the speckles of the N independent channels, the law of large numbers predicts a Gaussian distribution with variance of the order $1/N$. However, interference broadens the variance to $L/(\ell N)$ [7]. This was confirmed in a recent experiment of de Boer *et al.* [8]. Also in computer simulations by Edrei *et al.* the Gaussian behavior was observed, while a cross over to a log-normal distribution was seen for large disorder [9]. De Boer *et al.* also measured a small but clear deviation from a Gaussian, due interference of three transmission channels.

The third quantity which can be extracted is the conductance, which is obtained by summing also over all incoming directions. An extensive discussion of the distribution function of the conductance including a review was given by Altshuler *et al.* [10].

These three quantities are dominated by different interference processes. This can already be seen by considering their autocorrelation functions [11,12]. Let T_{ab} be the angular transmission coefficient for a speckle spot b arising from incoming wave a . Its correlator is called the C_1 correlation function. It is dominated by a *disconnected* diagram. The correlator of the total transmission $T_a = \sum_b T_{ab}$ is called the C_2 correlation, and dominated by the interference of two diffusons. In a diagrammatic approach it is a *connected, loopless* diagram. The interference process mixes two incoming into two outgoing diffusons. Finally, the correlator of the conductivity $T = \sum_{ab} T_{ab}$ is called C_3 correlation or Universal Conductance Fluctuation. It is dominated by a *connected loop* diagram.

We shall first calculate the distribution function of the total transmission. Subsequently we apply these ideas to the statistics of the angular transmission coefficient.

Consider a three dimensional slab with dimensions $W \times W \times L$, ($W \gg L$) with elastic scatterers at quenched random positions. We consider the ‘metallic’ regime, where the dimensionless conductance g is large. Let us look at the transmission problem for a scalar plane wave with unit incoming flux in channel a ,

$$\psi_a^{\text{in}}(\mathbf{r}) = \frac{1}{\sqrt{Ak\mu_a}} \exp(i\mathbf{q}_a \rho + ik\mu_a z) \quad z < 0, \quad (1)$$

where $A = W \times W$ denotes the area of the slab, k is the wavenumber, $\rho = (x, y)$ is the transversal coordinate and $\mu_a = \sqrt{1 - \mathbf{q}_a^2/k^2} = \cos \theta_a$, where θ_a is the angle with respect to the z -axis. The precise form of the propagators was derived in Ref. [13]. An incoming diffuson has the form

$$\mathcal{L}_a^{\text{in}}(\mathbf{r}) = \frac{4\pi\tau_1(\mu_a)}{k\ell A\mu_a} \frac{L - z}{L}, \quad (2)$$

where τ_1 describes the limit intensity of a semi-infinite system. We shall term the propagator summed over all incoming channels the ‘*total-flux diffuson*’:

$$\mathcal{L}^{\text{in}}(\mathbf{r}) \equiv \sum_a \mathcal{L}_a^{\text{in}}(\mathbf{r}) = \frac{4k}{\ell} \frac{L - z}{L}. \quad (3)$$

In the bulk the difference between a total-flux diffuson and a diffuson arising from plane wave incidence is just described by an overall factor ϵ_a ,

$$\mathcal{L}_a^{\text{in}}(\mathbf{r}) = \epsilon_a \mathcal{L}^{\text{in}}(\mathbf{r}), \quad (4)$$

with $\epsilon_a \equiv \tau_1(\mu_a)\pi/(k^2 A\mu_a)$ satisfying the sum rule $\sum_a \epsilon_a = 1$. Similarly, the outgoing diffusons are

$$\mathcal{L}_b^{\text{out}}(\mathbf{r}) = \epsilon_b \mathcal{L}^{\text{out}}(\mathbf{r}), \quad \mathcal{L}^{\text{out}}(\mathbf{r}) = \frac{k}{\ell} \frac{z}{L}. \quad (5)$$

The wave is transmitted into outgoing channel b with transmission amplitude $t_{ab} = 2k\sqrt{\mu_a\mu_b}G_{ab}$ and transmission probability $T_{ab} \equiv |t_{ab}|^2$. The average total transmission is obtained by summing all outgoing channels

$$\langle T_a \rangle = \langle \sum_b T_{ab} \rangle = \frac{\tau_1(\mu_a)\ell}{3L\mu_a}. \quad (6)$$

The average conductance is given by

$$g \equiv \sum_a \langle T_a \rangle = \frac{k^2 A \ell}{3\pi L}, \quad (7)$$

thus $\langle T_a \rangle = \epsilon_a g$, while one also has $\langle T_{ab} \rangle = \epsilon_a \epsilon_b g$ [13].

We consider the j^{th} cumulant of T_a . In a diagrammatic approach this object has j transmission amplitudes t_{ab} and an equal number of Hermitean conjugates $t_{ba}^\dagger = t_{ab}^*$. Explicit calculation for the second and third cumulant showed that the leading diagrams are connected, but have no loops [8]. We assume that this holds to any order. Let us fix the external diffusons in the term $t_{ab_1} t_{b_1 a}^\dagger t_{ab_2} \cdots t_{ab_j} t_{b_j a}^\dagger$. Contributions to the sum over b_i only come from diagrams with outgoing diffusons that have no transversal momentum. These are the diagrams where the lines with equal b_i are paired into diffusons. The outgoing diffusons are fixed now. For connected loopless diagrams there are $(j-1)!$ distinct choices for pairing the incoming amplitudes. Next we factor out the incoming and outgoing diffusons and group the remainder of the diagrams into a skeleton K . Making use of Eq. (4) we obtain:

$$\begin{aligned} \langle T_a^j \rangle_{\text{con}} = & \epsilon_a^j (j-1)! \int d\mathbf{r}_1 d\mathbf{r}'_1 \cdots d\mathbf{r}_j d\mathbf{r}'_j \mathcal{L}^{\text{in}}(\mathbf{r}_1) \mathcal{L}^{\text{out}}(\mathbf{r}'_1) \\ & \cdots \mathcal{L}^{\text{in}}(\mathbf{r}_j) \mathcal{L}^{\text{out}}(\mathbf{r}'_j) K(\mathbf{r}_1, \mathbf{r}'_1, \cdots, \mathbf{r}_j, \mathbf{r}'_j). \end{aligned} \quad (8)$$

The integral just describes

$$\langle \text{Tr}(tt^\dagger)^j \rangle \equiv \sum_{a_1, b_1, \dots, a_j, b_j} \langle t_{a_1 b_1} t_{b_1 a_2}^\dagger t_{a_2 b_2} \cdots t_{a_j b_j} t_{b_j a_1}^\dagger \rangle. \quad (9)$$

Indeed, for this quantity there is only one way to attach incoming and outgoing diffusons to K . The sums over the indices lead exactly to the total-flux diffusons in Eq. (8). We thus find

$$\langle T_a^j \rangle_{\text{con}} = (j-1)! \epsilon_a^j \langle \text{Tr}(tt^\dagger)^j \rangle, \quad (10)$$

which is the crucial step in the derivation. The eigenvalues T_n of the transmission matrix $t^\dagger t$ can be expressed as $T_n = 1/\cosh^2 L\gamma_n$. Under very general conditions [14] the distribution of the Lyapunov coefficients γ_n is uniform [1–3]. This implies that:

$$\langle \text{Tr}(tt^\dagger)^j \rangle = \langle \sum_{n=1}^N T_n^j \rangle = g \int_0^1 \frac{dT}{2T\sqrt{1-T}} T^j. \quad (11)$$

Normalizing with respect to the average, we introduce $s_a = T_a/\langle T_a \rangle$. The generating function of the connected diagrams is easily calculated

$$\begin{aligned} \Phi_{\text{con}}(x) & \equiv \sum_{j=1}^{\infty} \frac{(-1)^{j+1} x^j}{j!} \langle s_a^j \rangle_{\text{con}} \\ & = g \log^2 \left(\sqrt{1+x/g} + \sqrt{x/g} \right). \end{aligned} \quad (12)$$

Since the cumulants are solely given by connected diagrams, the distribution of s_a follows as

$$p(s_a) = \int_{-i\infty}^{i\infty} \frac{dx}{2\pi i} \exp[xs_a - \Phi_{\text{con}}(x)]. \quad (13)$$

For s_a near unity and large g we can expand Φ up to order x^2 , recovering the Gaussian behavior found by Kogan *et al.* [6]:

$$p(s_a) \approx \sqrt{\frac{3g}{4\pi}} \exp\left[-\frac{3g}{4}(s_a - 1)^2\right] \quad (14)$$

The integrand in Eq. (13) has a branch cut from $x = -g$ to $x = -\infty$. For $s_a \leq 0$ the contour can be closed to the right and $p(s_a)$ vanishes. The shape for small s_a (and large g) is dominated by a saddle point. One finds essentially a log-normal growth:

$$p(s_a) \sim \exp\left[\frac{g}{4} - \frac{g}{4}\left(\log \frac{2}{s_a} + \log \log \frac{2}{s_a} - 1\right)^2\right]. \quad (15)$$

Also for large s_a we can apply steepest descent. Here one finds a simple exponential decay

$$p(s_a) \approx \exp(-gs_a + g\frac{\pi^2}{4}), \quad s_a \gg 1. \quad (16)$$

In Fig. 1 we present the distribution (13) for some values of g . At moderate g the deviation from a Gaussian is clearly seen.

So far we have considered the case of an incoming plane wave. In optical systems a Gaussian intensity profile is more realistic. For perpendicular incidence the incoming amplitude is $\psi^{\text{in}}(\mathbf{r}) = W^{-1} \sum_a \phi(q_a) \psi_a^{\text{in}}(\mathbf{r})$, where $\psi_a^{\text{in}}(\mathbf{r})$ is the plane wave of Eq. (1), and where

$$\phi(q_a) = \sqrt{2\pi\rho_0} \exp\left(-\frac{1}{4}\rho_0^2 q_a^2\right). \quad (17)$$

We consider the limit where the beam is much broader than the sample thickness ($\rho_0 \gg L$) but still much smaller than the transversal size of the slab ($\rho_0 \ll W$). (A smaller beam diameter complicates the problem; when incoming transverse momenta, which are of order $1/\rho_0$, become of the order of $1/L$, the diffusons will take a different form [8]). Here the momentum dependence of the diffusons can be neglected. Due to integration over the center of gravity, each diagram involves a factor $A\delta_{\Sigma q, \Sigma q'}$. In the j^{th} order term there occurs a factor

$$\begin{aligned} F_j &= \frac{A}{A^{2j}} \sum_{q_1 q'_1 \dots q_j q'_j} \phi(q_1) \phi^*(q'_1) \dots \phi(q_j) \phi^*(q'_j) \delta_{\Sigma q, \Sigma q'} \\ &= \int d^2\rho |\phi(\rho)|^{2j}. \end{aligned} \quad (18)$$

For a plane wave we have $|\phi(\rho)| = \sqrt{A}$, and $F_j = A^{1-j}$. For our Gaussian beam we obtain

$$F_j = \frac{1}{j} \left(\frac{\pi\rho_0^2}{2}\right)^{1-j}. \quad (19)$$

It is thus convenient to identify $A_G = \frac{1}{2}\pi\rho_0^2$ with the effective area of a Gaussian beam. As compared to the plane wave case, the j^{th} order term is smaller by a factor $1/j$ for a Gaussian profile. This implies for the generating function of the connected diagrams

$$\Phi_{\text{con}}(x) = g \int_0^1 \frac{dy}{y} \log^2 \left(\sqrt{1 + \frac{xy}{g}} + \sqrt{\frac{xy}{g}} \right). \quad (20)$$

For small s_a (and large g) there is again a log-normal saddle point. For large s_a the dominant shape of the decay is given by the singularity at $x = -g$ and again yields $p(s_a) \sim \exp(-gs_a)$. In Fig. 2 we present the distribution function for different values of g .

By expansion of the generating function we recover the results for the second and third cumulant, obtained previously by de Boer *et al.* [8]

$$\langle s_a^2 \rangle_{\text{cum}} = \frac{2}{3g}, \quad \langle s_a^3 \rangle_{\text{cum}} = \frac{12}{5} \langle s_a^2 \rangle_{\text{cum}}^2 \quad (21)$$

for a plane wave. For a Gaussian beam we recover

$$\langle s_a^2 \rangle_{\text{cum}} = \frac{1}{3g}, \quad \langle s_a^3 \rangle_{\text{cum}} = \frac{16}{5} \langle s_a^2 \rangle_{\text{cum}}^2. \quad (22)$$

These last relations were confirmed experimentally [8].

We apply the same method for the distribution of the angular transmission coefficient. In the plane wave situation the average reads $\langle T_{ab} \rangle = \epsilon_a \epsilon_b g$. Let us count the number of connected loopless diagrams that contribute to $T_{ab}^j = t_{ab} t_{ba}^\dagger t_{ab} \cdots t_{ab} t_{ba}^\dagger$. In this case all pairings into outgoing diffusons contribute. This yields an extra combinatorial factor $j!$ in the j^{th} moment:

$$\langle T_{ab}^j \rangle_{\text{con}} = j!(j-1)! \epsilon_a^j \epsilon_b^j \langle \text{Tr}(t^\dagger t)^j \rangle. \quad (23)$$

For the normalized angular transmission coefficient $s_{ab} = T_{ab}/\langle T_{ab} \rangle$, we introduce the following generating function of the connected diagrams:

$$\Psi_{\text{con}}(x) \equiv \sum_{j=1}^{\infty} \frac{(-1)^{j-1} x^j}{j! j!} \langle s_{ab}^j \rangle_{\text{con}} \quad (24)$$

It is easy to see that

$$\Psi_{\text{con}}(x) = \Phi_{\text{con}}(x), \quad (25)$$

with Φ_{con} given by Eq. (12) for plane wave incidence and by Eq. (20) for a broad Gaussian beam, respectively. In contrast to the total-transmission distribution, the cumulants are not only given by the connected diagrams. Kogan *et al.* showed that the summation of the disconnected diagrams can be done elegantly by performing an additional integral. Using this result one gets

$$p(s_{ab}) = \int_0^\infty \frac{dv}{v} \int_{-i\infty}^{i\infty} \frac{dx}{2\pi i} \exp \left(-\frac{s_{ab}}{v} + xv - \Psi_{\text{con}}(x) \right). \quad (26)$$

The speckle intensity distribution is plotted in Fig. 3 for an incoming plane wave.

For large g and moderate s_{ab} we have $\Phi_{\text{con}}(x) \approx x$ and we recover the Rayleigh law: $p(s_{ab}) = \exp(-s_{ab})$. The leading correction is found by expanding in $1/g$

$$p(s_{ab}) = e^{-s_{ab}} \left[1 + \frac{1}{3g}(s_{ab}^2 - 4s_{ab} + 2) \right] \quad (27)$$

This was derived previously by Shnerb and Kaveh [4]; here we have related the prefactor of the correction term to the conductivity. Genack and Garcia fitted their data to this relation and found $g = 14.6$. Our Eq. (26) describes these data very well for $g = 14.4$.

For large s_{ab} one can again apply steepest descent, which yields

$$p(s_{ab}) \sim \exp(-2\sqrt{gs_{ab}}). \quad (28)$$

This stretched exponential tail differs from the form $p(s_{ab}) \sim \exp[-(81gs_{ab}^2/16)^{1/3}]$ asserted by Kogan *et al.* Their findings are based on truncating $\Phi_{\text{con}}(x)$ after order x^2 , which corresponds to including only the simplest connected diagram. Taking the full generating function into account, we find a qualitatively different saddle point.

A Gaussian profile of the incoming beam leads to a different distribution with the same asymptotic behavior.

Our results remain valid if there is a mismatch in the indices of refraction [13], but may change if the system is optically not very thick.

In conclusion, we have calculated the distribution function of the total amount of light transmitted through a disordered slab. It was related to the distribution function of the eigenvalues of the transmission matrix, which is known since the Lyapunov coefficients are uniformly distributed. Comparing to previous diagrammatic calculations [8] it became clear that this uniform distribution comes from summing connected, loopless diagrams.

Next we have calculated the distribution of the angular transmission intensity. Here a deviation from Rayleigh statistics is found, of new stretched exponential form. Our calculations are in agreement with measurements of both total and angular resolved transmission. As our results are based on loopless diagrams, they constitute the mean field expressions. Near the Anderson transition loop diagrams will change the distribution functions.

ACKNOWLEDGMENTS

Discussions with I. V. Lerner, B. L. Altshuler, and Yu. V. Nazarov are gratefully acknowledged. The research of Th. M. N. was supported by the Royal Netherlands Academy of Arts and Sciences (KNAW). This work was also sponsored by NATO (grant nr. CGR 921399).

REFERENCES

- [1] O. N. Dorokhov, Solid State Comm. **51**, 381 (1984).
- [2] J. B. Pendry, A. MacKinnon, and A. B. Pretre, Physica A **168**, 400 (1990).
- [3] A. D. Stone, P. A. Mello, K. A. Muttalib, and J.-L. Pichard, in *Mesoscopic phenomena in solids*, edited by B. L. Altshuler, P. A. Lee, and R. A. Webb (North-Holland, Amsterdam, 1991), Vol. 30, p. 369.
- [4] N. Shnerb and M. Kaveh, Phys. Rev. B **43**, 1279 (1991).
- [5] A. Z. Genack and N. Garcia, Europhys. Lett. **21**, 753 (1993).
- [6] E. Kogan, M. Kaveh, R. Baumgartner, and R. Berkovits, Phys. Rev. B **48**, 9404 (1993).
- [7] M. J. Stephen and G. Cwilich, Phys. Rev. Lett. **59**, 285 (1987).
- [8] J. F. de Boer *et al.*, submitted.
- [9] I. Edrei, M. Kaveh, and B. Shapiro, Phys. Rev. Lett. **62**, 2120 (1989).
- [10] B. L. Altshuler, V. E. Kravtsov, and I. V. Lerner, in *Mesoscopic phenomena in solids*, edited by B. L. Altshuler, P. A. Lee, and R. A. Webb (North-Holland, Amsterdam, 1991), Vol. 30, p. 449.
- [11] S. Feng, C. Kane, P. Lee, and A. D. Stone, Phys. Rev. Lett. **61**, 834 (1988).
- [12] P. A. Mello, E. Akkermans, and B. Shapiro, Phys. Rev. Lett. **61**, 459 (1988).
- [13] Th. M. Nieuwenhuizen and J. M. Luck, Phys. Rev. E **48**, 560 (1993).
- [14] Yu. V. Nazarov, submitted.

FIGURES

FIG. 1. Intensity distribution of the total transmission, in units of $\sqrt{3g/4\pi}$, versus the normalized intensity s_a for an incoming plane wave. With $g = 2, 4, 16$, and 64 (upper to lower curve).

FIG. 2. Intensity distribution of the total transmission, in units of $\sqrt{3g/2\pi}$, versus the normalized intensity s_a for an incoming wave with Gaussian profile. With $g = 2, 4, 16$, and 64 (upper to lower curve).

FIG. 3. Intensity distribution of speckles versus the normalized intensity s_{ab} for an incoming plane wave. With $g = 2, 4$, and 8 (upper to lower curve at $s_{ab} = 5$). The dashed line corresponds to the Rayleigh law ($g = \infty$).





